



适合贴片机组装 Suitable for SMT

短小轻薄 Small Size& Light Weight

符合RoHS和无卤标准 Meet RoHS& HF

Standard Electrical Specifications 标准电气规范

Item Type	Rated Power at 70°C 额定功率	Max Working voltage 最大工作电压	Max Over load voltage 最大过负荷电压	T.C.R (PPM/°C) 温度系数	Resistance Range 阻值范围		
					B(±0.1%)	F(±1%)	J(±5%)
					D(±0.5%)	G(±2%)	K(±10%)
CL0201	0.05W	25V	50V	±200	—	1Ω~9.9Ω	1Ω~9.9Ω
					—	10Ω~1MΩ	10Ω~1MΩ
CL0402	0.0625W	50V	100V	±200	—	1Ω~9.9Ω	1Ω~9.9Ω
					10Ω~1MΩ	10Ω~1MΩ	10Ω~10MΩ
CL0603	0.1W	75V	150V	±200	—	1Ω~9.9Ω	1Ω~9.9Ω
				±100	10Ω~1MΩ	10Ω~1MΩ	10Ω~10MΩ
CL0805	0.125W	150V	300V	±200	—	1Ω~9.9Ω	1Ω~9.9Ω
				±100	10Ω~1MΩ	10Ω~1MΩ	10Ω~10MΩ
CL1206	0.25W	200V	400V	±200	—	1Ω~9.9Ω	1Ω~9.9Ω
				±100	10Ω~1MΩ	10Ω~1MΩ	10Ω~10MΩ
CL1210	0.5W	200V	400V	±200	—	1Ω~9.9Ω	1Ω~9.9Ω
				±100	10Ω~1MΩ	10Ω~1MΩ	10Ω~10MΩ
CL2010	0.75W	200V	400V	±200	—	1Ω~9.9Ω	1Ω~9.9Ω
				±100	10Ω~1MΩ	10Ω~1MΩ	10Ω~10MΩ
CL2512	1W	200V	400V	±200	—	1Ω~9.9Ω	1Ω~9.9Ω
				±100	10Ω~1MΩ	10Ω~1MΩ	10Ω~10MΩ

For non-standard parts, please contact our sales dept

关于非标部分请联系我们销售部

Operating Temperature Range:-55°C~+155°C

工作温度范围:-55°C~+155°C

Type	0201	0402	0603	0805	1206	1210	2010	2512
Jumper Resistance Value 跨接电阻评价	1% < 30mΩ			5% < 50mΩ				
Jumper Rated Current 跨接电阻额定电流	0.5A	1A		2A				
Max imam Over Load Voltage 最高过负荷电流	1A	2A		5A	10A			